


Authorised New Zealand Distributor Ph (09) 483 4000 www.firestopcentre.co.nz

### Installation Instructions

- 1. Ensure the faces of the aperture opening are free of dust and any other contaminants. The faces may be moistened for better adhesion.
- 2. The seal can be positioned to either side of the construction or anywhere inbetween.
- 3. Install a stone wool shutter board to achieve the required thickness of mortar. Make sure that this achieves a very tight seal - any small openings should be sealed with Protecta® FR Acrylic
- 4. Pour clean water into a suitable mixing vessel and pour enough mortar to obtain the required consistency. Mix well to avoid lumps. Always add the mortar to the water, do not reverse this mixing process.
- 5. Once the desired consistency is achieved pour or trowel the mortar onto the shutter board making sure that it flows into all corners and around services. Apply a firm pressure to the mortar to eliminate any trapped air bubbles. Build up to the required depth.



Protecta EX Mortar Minimum seal depth 100mm Maximum aperture 1200x2400mm

# 

As a part of our policy of on-going product development and testing, we reserve the right to modify, alter or change product specifications without giving notice. All information contained in this document is given in good faith and is provided for guidance only. Any drawings provided are for illustrative purposes only. As Polyseam has no control over the methods or competence of installation and of prevailing site conditions, no warranties, expressed or implied, is intended to be given as to the actual performance of the product mentioned or referred to herein and no liability whatsoever will be accepted for any loss, damage or injury arising from the use of the information given.

FAS 210027 AS1530.4-2014 AS4072.1-2005

For all technical details on the products specified please refer to the technical data sheets that can be found on www.firestopcentre.co.nz

Signed and approved:

## warringtonfire

FAS 210027 Page 20 AS1530.4-2014 AS4072.1-2005

### System ID# FC265

**Products** 

Protecta EX Mortar

Stone wool shutter

**Application** 

Fire stopping of blanks

in rigid walls

Construction

Minimum wall thickness of 150mm and comprise aerated concrete or concrete with a minimum density of 650kg/m<sup>3</sup>.

### Fire & Sound classification

Blank seal

FRR -240/240

Sound reduction (seal only)

STC 64



Polyseam Ltd. 15 St Andrews Road Huddersfield, West Yorkshire, HD1 6SB Email: post.uk@polyseam.com

Sheet size:	Drawn date & no:
<b>A4</b>	23/5/21
	Drawn by:
	K.B