

# Regulatory Information Report

**RIR2207701**

## Fire Resistance Test for Penetrations in FR Plasterboard Wall

|              |                     |
|--------------|---------------------|
| Issued to:   | Firestop Centre Ltd |
| Test method: | AS1530.4-2014       |
| Report Date: | 08/07/2025          |
| Test number: | PF22077             |

# Table of Contents

|      |                                                       |    |
|------|-------------------------------------------------------|----|
| 1.1  | Document revision schedule .....                      | 4  |
| 1.2  | Signatories .....                                     | 4  |
| 2.   | Report Summary .....                                  | 5  |
| 3.   | General Information .....                             | 6  |
| 3.1  | Testing Scope .....                                   | 6  |
| 3.2  | Contact Details .....                                 | 6  |
| 3.3  | Specimen Preparation, Conditioning and Timeline ..... | 7  |
| 3.4  | Use of the Report .....                               | 7  |
| 4.   | Specimen Description .....                            | 8  |
| 4.1  | Supporting Construction .....                         | 8  |
| 4.2  | Specimen A .....                                      | 9  |
| 4.3  | Specimen B .....                                      | 9  |
| 4.4  | Specimen C .....                                      | 9  |
| 4.5  | Specimen D .....                                      | 10 |
| 4.6  | Specimen E .....                                      | 11 |
| 4.7  | Specimen F .....                                      | 11 |
| 4.8  | Specimen G .....                                      | 11 |
| 4.9  | Specimen H .....                                      | 12 |
| 4.10 | Specimen I .....                                      | 12 |
| 4.11 | Specimen J .....                                      | 13 |
| 5.   | Test Results .....                                    | 14 |
| 5.1  | Observations during the test .....                    | 14 |
| 5.2  | Specimen A – 40mm Horizontal linear gap .....         | 15 |
| 5.3  | Specimen B – 20mm Cable bundle .....                  | 16 |

|      |                                      |    |
|------|--------------------------------------|----|
| 5.4  | Specimen C – 150DN Copper Pipe ..... | 17 |
| 5.5  | Specimen D – 100DN Copper Pipe ..... | 18 |
| 5.6  | Specimen E – Single Cable.....       | 19 |
| 5.7  | Specimen F – 5mm Cable bundle.....   | 20 |
| 5.8  | Specimen G – 35mm Cable bundle ..... | 21 |
| 5.9  | Specimen H – NB32 Steel Pipe .....   | 22 |
| 5.10 | Specimen I – 20mm Cable bundle ..... | 23 |
| 5.11 | Specimen J – 35mm Cable bundle ..... | 24 |
| 6.   | Photos .....                         | 25 |

## 1.1 Document revision schedule

| Revision # | Date       | Description |
|------------|------------|-------------|
| 1          | 08/07/2025 | Issued      |

## 1.2 Signatories

| Report         | Name                                  | Signature                                                                          | Date       |
|----------------|---------------------------------------|------------------------------------------------------------------------------------|------------|
| Prepared by:   | Alexey Kokorin                        |  | 08/07/2025 |
| Authorised by: | Andrew Bain<br>(Authorized signatory) |  | 08/07/2025 |



All tests reported herein  
have been performed in  
accordance with the  
laboratory's scope of  
accreditation

## 2. Report Summary

A 64mm steel stud frame, lined with 2 x 13mm FR plasterboard on each side was constructed and installed below a 150mm concrete slab lintel. Steel studs were installed to accommodate a horizontal linear gap along the lintel, cable bundles, copper pipes and a steel pipe. A deflection head track was installed directly to the lintel and bottom of the refractory frame, with studs between. The plasterboard was trimmed and installed 40mm below the lintel, resulting in a 40mm horizontal linear gap on top of the deflection head track.

Additional penetrations for 5 x cable bundles, 2 x copper pipes and 1 x steel pipe were cut. All services were protected using FIRESTOP Ultra sealant with or without ceramic fibre blanket.

| Specimen | Joint                      | Actual Integrity (min) | Actual Insulation (min) | FRL       |
|----------|----------------------------|------------------------|-------------------------|-----------|
| <b>A</b> | 40mm horizontal linear gap | 123 NF                 | 123 NF                  | -/120/120 |
| <b>B</b> | 20mm Cable Bundle          | 123 NF                 | 123 NF                  | -/120/120 |
| <b>C</b> | DN150 Copper pipe          | 123 NF                 | 70                      | -/120/60  |
| <b>D</b> | DN100 Copper pipe          | 123 NF                 | 96                      | -/120/90  |
| <b>E</b> | Single Cable               | 123 NF                 | 123 NF                  | -/120/120 |
| <b>F</b> | 5mm Cable Bundle           | 123 NF                 | 123 NF                  | -/120/120 |
| <b>G</b> | 35mm Cable Bundle          | 123 NF                 | 123 NF                  | -/120/120 |
| <b>H</b> | 32 NB Steel pipe           | 123 NF                 | 123 NF                  | -/120/120 |
| <b>I</b> | 20mm Cable Bundle          | 123 NF                 | 123 NF                  | -/120/120 |
| <b>J</b> | 35mm Cable Bundle          | 123 NF                 | 123 NF                  | -/120/120 |

NF indicates no failures observed during test

## 3. General Information

---

### 3.1 Testing Scope

**Applicable Standards:**

AS 1530-2014 Part 4: Section 10 Service penetrations and control joints.

AS 4072.1-2005 Part 1: Service penetrations and control joints

**Departures from Testing Method:**

No departures from the testing method

**Test conditions:**

Conditions complied with the Standard

### 3.2 Contact Details

**Accredited Testing Laboratory**

FTSL - Passive Fire Inspection and Test Services Ltd

Accreditation Number - 1335

1/113 Pavilion Drive, Mangere, Auckland, 2022

New Zealand

Contact e-mail: [tests@firelab.co.nz](mailto:tests@firelab.co.nz)

**Issued to:**

Firestop Centre Ltd.

657 Great South Rd, Penrose, Auckland, 1061

New Zealand

Contact e-mail: [info@firestopcentre.co.nz](mailto:info@firestopcentre.co.nz)

### 3.3 Specimen Preparation, Conditioning and Timeline

#### **Specimens conditioning and delivery to Laboratory:**

Separating element was built by the Laboratory in line with Client instructions. Installation of fire stopping system was performed by Laboratory in line with Client instructions. The Laboratory was not involved in sampling of the materials. The Laboratory checked materials during construction of the specimen.

#### **Testing date:**

28/02/2023

#### **Installation completion date:**

22/01/2023

#### **Termination of The Test:**

The test was discontinued at 123 minutes.

### 3.4 Use of the Report

A regulatory information report was issued in addition to the full test report PF22077. This provides the minimum information required for regulatory compliance

This report shall not be reproduced, except in full.

The specimen was a symmetrical construction. The results of the test apply if exposed to fire from either side. This report details the methods of construction, test conditions and the results obtained when the specific element of construction described herein was tested following the procedure outlined in AS 1530.4. Any significant variation with respect to size, constructional details, loads, stresses, edge or end conditions, other than that allowed under the field of direct application in the relevant test method, is not covered by this report.

Because of the nature of fire resistance testing and the consequent difficulty in quantifying the uncertainty of measurement of fire resistance, it is not possible to provide a stated degree of accuracy of the result.

The test results relate to the specimens of the product in the form in which they were tested. Differences in the composition or thickness of the product may significantly affect the performance during the test and may therefore invalidate the test results. Care should be taken to ensure that any product, which is supplied or used, is fully represented by the specimens, which were tested.

The specimens were supplied by the sponsor and the Laboratory was not involved in any of selection or sampling procedures. The results of these fire tests may be used

to directly assess fire hazard, but it should be recognized that a single test method will not provide a full assessment of fire hazard under all fire conditions.

## 4. Specimen Description

### 4.1 Supporting Construction

| Separating Element |                     |                                                  |
|--------------------|---------------------|--------------------------------------------------|
| 1.1                | Item / Product Name | Steel Stud and Plasterboard Separating element   |
|                    | Measurements        | Width / Height (W/H): 1200mm x 1200mm            |
|                    |                     | Wall Thickness: 116mm                            |
|                    |                     | Cavity: 64mm                                     |
| 1.2                | Item / Product Name | Steel Stud                                       |
|                    | Measurements        | Width / Height (W/H): 64mm x 35.5mm              |
|                    |                     | Thickness (T): 0.50BMT                           |
|                    | Additional Info     | Used to construct separating element             |
| 1.3                | Item / Product Name | Steel Deflection Track                           |
|                    | Measurements        | Width / Height (W/H): 64mm x 50mm                |
|                    |                     | Thickness (T): 0.75BMT                           |
|                    | Additional Info     | Used to construct separating element             |
| 1.4                | Item / Product Name | 13mm FR Plasterboard                             |
|                    | Measurements        | Width / Height (W/H): 1200mm x 3000mm            |
|                    |                     | Thickness (T): 13mm                              |
|                    | Additional Info     | 2 x layers installed to each side of steel frame |
| 1.5                | Item / Product Name | Concrete Slab                                    |
|                    | Measurements        | Width / Length (W/L): 1200mm x 490mm             |
|                    |                     | Thickness (T): 150mm                             |
|                    | Additional Info     | Used to construct separating element             |
| 4.1                | Item / Product Name | Self-Tapping Screws                              |
|                    | Measurements        | 32mm                                             |
|                    | Installation        | Used to fix plasterboard to steel stud           |

|     |                     |                                         |
|-----|---------------------|-----------------------------------------|
| 4.2 | Item / Product Name | Self-Tapping Screws                     |
|     | Measurements        | 41mm                                    |
|     | Installation        | Used to fix plasterboard to steel stud  |
| 4.3 | Item / Product Name | Metal Screw – Button Head Philips drive |
|     | Measurements        | 8g x 25mm                               |
|     | Installation        | Used to fix framing components          |

#### 4.2 Specimen A

|     |                     |                                                                                            |
|-----|---------------------|--------------------------------------------------------------------------------------------|
| 3.1 | Item / Product Name | Formulation F023SDW01 - FIRESTOP Ultra sealant                                             |
|     | Dimensions          | 600mL                                                                                      |
|     | Installation        | Installed ontop of deflection head track to create a 26mm depth horizontal linear gap seal |

#### 4.3 Specimen B

|     |                     |                                                  |
|-----|---------------------|--------------------------------------------------|
| 3.1 | Item / Product Name | Formulation F023SDW01 - FIRESTOP Ultra sealant   |
|     | Dimensions          | 600mL                                            |
|     | Installation        | Installed into annular gap + 50 x 70mm cone      |
| 2.1 | Item / Product Name | Cat6 Cable                                       |
|     | Measurements        | Outer Diameter (OD): 6.5mm (nominal)             |
|     | Additional Info     | 8 x cables installed in deflection head aperture |

#### 4.4 Specimen C

|     |                     |                                                |
|-----|---------------------|------------------------------------------------|
| 3.1 | Item / Product Name | Formulation F023SDW01 - FIRESTOP Ultra sealant |
|     | Dimensions          | 600mL                                          |
|     | Installation        | Installed into annular gap + 50 x 70mm cone    |
| 2.2 | Item / Product Name | DN150 Copper Pipe                              |
|     | Measurements        | Outer Diameter (OD): 153mm                     |
|     |                     | Inner Diameter (ID): 148mm                     |
|     |                     | Thickness (T): 2.5mm                           |

|  |                 |                            |
|--|-----------------|----------------------------|
|  | Additional Info | Installed through aperture |
|--|-----------------|----------------------------|

|     |                     |                                                                                                         |
|-----|---------------------|---------------------------------------------------------------------------------------------------------|
| 5.1 | Item / Product Name | Ceramic Fibre Blanket                                                                                   |
|     | Measurements        | Width / Height (W/H): 610mm x 7200mm                                                                    |
|     |                     | Thickness (T): 25mm                                                                                     |
|     |                     | Density ( $\rho$ ): 128Kg/m <sup>3</sup>                                                                |
|     | Additional Info     | Wrapped around service 2 x times with additional 150mm overlap, extending 300mm from separating element |
| 4.4 | Item / Product Name | Stainless-Steel Cable Ties                                                                              |
|     | Measurements        | 10mm x 1000mm                                                                                           |
|     | Installation        | Used to fix wrap around services 100mm from ends of wrap                                                |

#### 4.5 Specimen D

|     |                     |                                                                                                         |
|-----|---------------------|---------------------------------------------------------------------------------------------------------|
| 3.1 | Item / Product Name | Formulation F023SDW01 - FIRESTOP Ultra sealant                                                          |
|     | Dimensions          | 600mL                                                                                                   |
|     | Installation        | Installed in annular gap + 50x70mm cone                                                                 |
| 2.3 | Item / Product Name | DN100 Copper Pipe                                                                                       |
|     | Measurements        | Outer Diameter (OD): 102mm                                                                              |
|     |                     | Inner Diameter (ID): 98mm                                                                               |
|     |                     | Thickness (T): 2.25mm                                                                                   |
|     | Additional Info     | Installed through aperture                                                                              |
| 5.1 | Item / Product Name | Ceramic Fibre Blanket                                                                                   |
|     | Measurements        | Width / Height (W/H): 610mm x 7200mm                                                                    |
|     |                     | Thickness (T): 25mm                                                                                     |
|     |                     | Density ( $\rho$ ): 128Kg/m <sup>3</sup>                                                                |
|     | Additional Info     | Wrapped around service 2 x times with additional 150mm overlap, extending 300mm from separating element |
| 4.4 | Item / Product Name | Stainless-Steel Cable Ties                                                                              |
|     | Measurements        | 10mm x 1000mm                                                                                           |

|  |              |                                                          |
|--|--------------|----------------------------------------------------------|
|  | Installation | Used to fix wrap around services 100mm from ends of wrap |
|--|--------------|----------------------------------------------------------|

#### 4.6 Specimen E

|     |                     |                                                |
|-----|---------------------|------------------------------------------------|
| 3.1 | Item / Product Name | Formulation F023SDW01 - FIRESTOP Ultra sealant |
|     | Dimensions          | 600mL                                          |
|     | Installation        | Installed in annular gap + 50x70mm cone        |
| 2.4 | Item / Product Name | TPS Cable                                      |
|     | Measurements        | Width / Height (W/H): 12.5mm x 5mm             |
|     | Additional Info     | 1 x cable installed through aperture           |

#### 4.7 Specimen F

|     |                     |                                                |
|-----|---------------------|------------------------------------------------|
| 3.1 | Item / Product Name | Formulation F023SDW01 - FIRESTOP Ultra sealant |
|     | Dimensions          | 600mL                                          |
|     | Installation        | Installed in annular gap + 50x70mm cone        |
| 2.4 | Item / Product Name | Nexans OLEX TPS Cable                          |
|     | Measurements        | Width / Height (W/H): 12.5mm x 5mm             |
|     | Additional Info     | 2 x cables installed through aperture          |

#### 4.8 Specimen G

|     |                     |                                                |
|-----|---------------------|------------------------------------------------|
| 3.1 | Item / Product Name | Formulation F023SDW01 - FIRESTOP Ultra sealant |
|     | Dimensions          | 600mL                                          |
|     | Installation        | Installed in annular gap + 50x70mm cone        |
| 2.1 | Item / Product Name | Cat6 Cable                                     |
|     | Measurements        | Outer Diameter (OD): 6.5mm (nominal)           |
|     | Additional Info     | 16 x cables installed through aperture         |

## 4.9 Specimen H

|     |                     |                                                                                                         |
|-----|---------------------|---------------------------------------------------------------------------------------------------------|
| 3.1 | Item / Product Name | Formulation F023SDW01 - FIRESTOP Ultra sealant                                                          |
|     | Dimensions          | 600mL                                                                                                   |
|     | Installation        | Installed in annular gap + 50x70mm cone                                                                 |
| 2.5 | Item / Product Name | 32NB Steel Pipe                                                                                         |
|     | Measurements        | Outer Diameter (OD): 42.5mm                                                                             |
|     |                     | Inner Diameter (ID): 36mm                                                                               |
|     |                     | Thickness (T): 3.25mm                                                                                   |
|     | Additional Info     | Installed through aperture                                                                              |
| 5.1 | Item / Product Name | Ceramic Fibre Blanket                                                                                   |
|     | Measurements        | Width / Height (W/H): 610mm x 7200mm                                                                    |
|     |                     | Thickness (T): 25mm                                                                                     |
|     |                     | Density ( $\rho$ ): 128Kg/m <sup>3</sup>                                                                |
|     | Additional Info     | Wrapped around service 2 x times with additional 150mm overlap, extending 300mm from separating element |
| 4.4 | Item / Product Name | Stainless-Steel Cable Ties                                                                              |
|     | Measurements        | 10mm x 1000mm                                                                                           |
|     | Installation        | Used to fix wrap around services 100mm from ends of wrap                                                |

## 4.10 Specimen I

|     |                     |                                                |
|-----|---------------------|------------------------------------------------|
| 3.1 | Item / Product Name | Formulation F023SDW01 - FIRESTOP Ultra sealant |
|     | Dimensions          | 600mL                                          |
|     | Installation        | Installed in annular gap + 50x70mm cone        |
| 2.1 | Item / Product Name | Cat6 Cable                                     |
|     | Measurements        | Outer Diameter (OD): 6.5mm (nominal)           |
|     | Additional Info     | 8 x cables installed through aperture          |

#### 4.11 Specimen J

|     |                     |                                                |
|-----|---------------------|------------------------------------------------|
| 3.1 | Item / Product Name | Formulation F023SDW01 - FIRESTOP Ultra sealant |
|     | Dimensions          | 600mL                                          |
|     | Installation        | Installed in annular gap + 50x70mm cone        |
| 2.1 | Item / Product Name | Cat6 Cable                                     |
|     | Measurements        | Outer Diameter (OD): 6.5mm (nominal)           |
|     | Additional Info     | 16 x cables installed through aperture         |

## 5. Test Results

### 5.1 Observations during the test

| Time Minutes | Test Face | SP               | Observations                                        |
|--------------|-----------|------------------|-----------------------------------------------------|
| 2            | U         | G, I, J          | Smoke from between cables                           |
| 8            | U         | A                | Smoke from between cables                           |
| 9            | U         | C, D             | Smoke from end of pipe                              |
| 10           | E         | B, E, F, G, I, J | Visible charring/discolouring of sealant cone       |
| 10           | E         | B, E, F, G, I, J | Cables have combusted and are deforming             |
| 20           | U         | ALL              | No notable changes                                  |
| 30           | E         | A                | Combustion of sealant, visible discolouring         |
| 45           | U         | ALL              | No notable changes                                  |
| 60           | U         | ALL              | No notable changes                                  |
| 75           | U         | ALL              | No notable changes                                  |
| 90           | U         | ALL              | No notable changes                                  |
| 95           | U         | A                | Visible expansion of sealant cone, crack in sealant |
| 120          | U         | H                | Crack between sealant and wrap junction             |
| 120          | U         | C                | Discolouring of copper pipe 200mm from wrap         |
| 123          |           |                  | TEST DISCONTINUED                                   |

**NOTE: E – Exposed Face (inside furnace),  
U – Unexposed Face (outside furnace)  
SE – Separating element**

## 5.2 Specimen A – 40mm Horizontal linear gap

|                                       |                                                                                                                                                                                                                                                  |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Service                               | 40mm wide Horizontal Linear Gap seal                                                                                                                                                                                                             |
| Joint Details                         | Sealant (3.1)                                                                                                                                                                                                                                    |
| <b>Local Fire-stopping Protection</b> |                                                                                                                                                                                                                                                  |
| Application                           | Symmetrical                                                                                                                                                                                                                                      |
| Protection Used                       | The top of the plasterboard was measured to be 40mm below the concrete slab, exposing the deflection head track. Sealant (3.1) was applied on top of the deflection head track, flush with the plasterboard, resulting in a 26mm (nominal) seal. |

|                            |                              |
|----------------------------|------------------------------|
| <b>Structural adequacy</b> | <b>Not applicable</b>        |
| <b>Integrity</b>           | <b>No failure at 123 min</b> |
| <b>Insulation</b>          | <b>No failure at 123 min</b> |



### 5.3 Specimen B – 20mm Cable bundle

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Service                               | 20mm Cable Bundle                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Service Details                       | 8 x Cable (2.1), Sealant (3.1)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Aperture Size                         | 30mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Annular Spacing                       | Min: 2mm, Max: 4mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>Local Fire-stopping Protection</b> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Application                           | Symmetrical                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Protection Used                       | Aperture was cut into the deflection head track, between the concrete slab and the plasterboard. 8 x cables (2.1) were bundled together (25mm nominal bundle OD), then passed through the aperture, extending 500mm from the exposed face. Sealant was applied on top of the deflection head track, flush with the plasterboard, resulting in a 26mm (nominal) seal. An additional 50mm x 70mm cone of sealant was applied between the cable bundle and separating element. The cone extended 50mm from the cable bundle onto the separating element, and 70mm along the cable bundle. |

|                            |                              |
|----------------------------|------------------------------|
| <b>Structural adequacy</b> | <b>Not applicable</b>        |
| <b>Integrity</b>           | <b>No failure at 123 min</b> |
| <b>Insulation</b>          | <b>No failure at 123 min</b> |



## 5.4 Specimen C – 150DN Copper Pipe

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Service                               | DN150 Copper pipe                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Service Details                       | Pipe (2.2), Sealant (3.1), Ceramic Fibre Blanket (5.1), Cable Ties (4.4)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Aperture Size                         | 153mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Annular Spacing                       | Min: 0mm, Max: 1mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Local Fire-stopping Protection</b> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Application                           | Symmetrical                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Protection Used                       | Aperture was cut into the separating element. The pipe (2.8) was placed through the aperture, extending 500mm from the exposed face. A 50mm x 70mm cone of sealant was applied between the pipe and separating element. The cone extended 50mm from the pipe onto the separating element, and 70mm along the pipe. Once the sealant had cured, the cable tray was wrapped with ceramic blanket (5.1). Two revolutions were applied around the pipe, with 150mm (nominal) overlap. The wrap extended 300mm from the separating element, and was secured using two cable ties, spaced 100mm from each end of the wrap. |

|                            |                              |
|----------------------------|------------------------------|
| <b>Structural adequacy</b> | <b>Not applicable</b>        |
| <b>Integrity</b>           | <b>No failure at 123 min</b> |
| <b>Insulation</b>          | <b>70 min</b>                |

## 5.5 Specimen D – 100DN Copper Pipe

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Service                               | DN100 Copper pipe                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Service Details                       | Pipe (2.3), Sealant (3.1), Ceramic Fibre Blanket (5.1), Cable Ties (4.4)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Aperture Size                         | 102mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Annular Spacing                       | Min: 0mm, Max: 1mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Local Fire-stopping Protection</b> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Application                           | Symmetrical                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Protection Used                       | Aperture was cut into the separating element. The pipe (2.8) was placed through the aperture, extending 500mm from the exposed face. A 50mm x 70mm cone of sealant was applied between the pipe and separating element. The cone extended 50mm from the pipe onto the separating element, and 70mm along the pipe. Once the sealant had cured, the cable tray was wrapped with ceramic blanket (5.1). Two revolutions were applied around the pipe, with 150mm (nominal) overlap. The wrap extended 300mm from the separating element, and was secured using two cable ties, spaced 100mm from each end of the wrap. |

|                            |                              |
|----------------------------|------------------------------|
| <b>Structural adequacy</b> | <b>Not applicable</b>        |
| <b>Integrity</b>           | <b>No failure at 123 min</b> |
| <b>Insulation</b>          | <b>96 min</b>                |

## 5.6 Specimen E – Single Cable

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Service                               | Single Cable                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Service Details                       | 1 x Cable (2.4), Sealant (3.1)                                                                                                                                                                                                                                                                                                                                                                                                                |
| Aperture Size                         | 25mm                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Annular Spacing                       | Min: 10mm, Max: 16mm                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Local Fire-stopping Protection</b> |                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Application                           | Symmetrical                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Protection Used                       | Aperture was cut into the separating element. 1 x cable (2.4) was passed through the aperture, extending 500mm from the exposed face. Sealant was installed in the annular gap, flush with the plasterboard, resulting in a 26mm (nominal) seal. An additional 50mm x 70mm cone of sealant was applied between the cable and separating element. The cone extended 50mm from the cable onto the separating element, and 70mm along the cable. |

|                            |                              |
|----------------------------|------------------------------|
| <b>Structural adequacy</b> | <b>Not applicable</b>        |
| <b>Integrity</b>           | <b>No failure at 123 min</b> |
| <b>Insulation</b>          | <b>No failure at 123 min</b> |

## 5.7 Specimen F – 5mm Cable bundle

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Service                               | 5mm Cable Bundle                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Service Details                       | 2 x Cable (2.4), Sealant (3.1)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Aperture Size                         | 25mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Annular Spacing                       | Min: 8mm, Max: 10mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Local Fire-stopping Protection</b> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Application                           | Symmetrical                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Protection Used                       | Aperture was cut into the separating element. 2 x cables (2.1) were bundled together (14mm nominal bundle OD), then passed through the aperture, extending 500mm from the exposed face. Sealant was installed in the annular gap, flush with the plasterboard, resulting in a 26mm (nominal) seal. An additional 50mm x 70mm cone of sealant was applied between the cable bundle and separating element. The cone extended 50mm from the cable bundle onto the separating element, and 70mm along the cable bundle. |

|                            |                              |
|----------------------------|------------------------------|
| <b>Structural adequacy</b> | <b>Not applicable</b>        |
| <b>Integrity</b>           | <b>No failure at 123 min</b> |
| <b>Insulation</b>          | <b>No failure at 123 min</b> |



## 5.8 Specimen G – 35mm Cable bundle

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Service                               | 35mm Cable Bundle                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Service Details                       | 16 x Cable (2.1), Sealant (3.1)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Aperture Size                         | 50mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Annular Spacing                       | Min: 5mm, Max: 8mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Local Fire-stopping Protection</b> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Application                           | Symmetrical                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Protection Used                       | Aperture was cut into the separating element. 16 x cables (2.1) were bundled together (40mm nominal bundle OD), then passed through the aperture, extending 500mm from the exposed face. Sealant was installed in the annular gap, flush with the plasterboard, resulting in a 26mm (nominal) seal. An additional 50mm x 70mm cone of sealant was applied between the cable bundle and separating element. The cone extended 50mm from the cable bundle onto the separating element, and 70mm along the cable bundle. |

|                            |                              |
|----------------------------|------------------------------|
| <b>Structural adequacy</b> | <b>Not applicable</b>        |
| <b>Integrity</b>           | <b>No failure at 123 min</b> |
| <b>Insulation</b>          | <b>No failure at 123 min</b> |

## 5.9 Specimen H – NB32 Steel Pipe

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Service                               | 32 NB Steel pipe                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Service Details                       | Pipe (2.3), Sealant (3.1), Ceramic Fibre Blanket (5.1), Cable Ties (4.4)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Aperture Size                         | 58mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Annular Spacing                       | Min: 7mm, Max: 9mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Local Fire-stopping Protection</b> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Application                           | Symmetrical                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Protection Used                       | Aperture was cut into the separating element. The pipe (2.8) was placed through the aperture, extending 500mm from the exposed face. A 50mm x 70mm cone of sealant was applied between the pipe and separating element. The cone extended 50mm from the pipe onto the separating element, and 70mm along the pipe. Once the sealant had cured, the cable tray was wrapped with ceramic blanket (5.1). Two revolutions were applied around the pipe, with 150mm (nominal) overlap. The wrap extended 300mm from the separating element, and was secured using two cable ties, spaced 100mm from each end of the wrap. |

|                            |                              |
|----------------------------|------------------------------|
| <b>Structural adequacy</b> | <b>Not applicable</b>        |
| <b>Integrity</b>           | <b>No failure at 123 min</b> |
| <b>Insulation</b>          | <b>No failure at 123 min</b> |



## 5.10 Specimen I – 20mm Cable bundle

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Service                               | 20mm Cable Bundle                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Service Details                       | 8 x Cable (2.1), Sealant (3.1)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Aperture Size                         | 30mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Annular Spacing                       | Min: 0mm, Max: 4mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Local Fire-stopping Protection</b> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Application                           | Symmetrical                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Protection Used                       | Aperture was cut into the separating element. 8 x cables (2.1) were bundled together (25mm nominal bundle OD), then passed through the aperture, extending 500mm from the exposed face. Sealant was installed in the annular gap, flush with the plasterboard, resulting in a 26mm (nominal) seal. An additional 50mm x 70mm cone of sealant was applied between the cable bundle and separating element. The cone extended 50mm from the cable bundle onto the separating element, and 70mm along the cable bundle. |

|                            |                              |
|----------------------------|------------------------------|
| <b>Structural adequacy</b> | <b>Not applicable</b>        |
| <b>Integrity</b>           | <b>No failure at 123 min</b> |
| <b>Insulation</b>          | <b>No failure at 123 min</b> |



### 5.11 Specimen J – 35mm Cable bundle

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Service                               | 35mm Cable Bundle                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Service Details                       | 16 x Cable (2.4), Sealant (3.1)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Aperture Size                         | 30mm x 70mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Annular Spacing                       | Min: 5mm, Max: 10mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Local Fire-stopping Protection</b> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Application                           | Symmetrical                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Protection Used                       | Aperture was cut into the separating element. 16 x cables (2.1) were bundled together (20mm x 50mm nominal bundle OD), then passed through the aperture, extending 500mm from the exposed face. Sealant was installed in the annular gap, flush with the plasterboard, resulting in a 26mm (nominal) seal. An additional 50mm x 70mm cone of sealant was applied between the cable bundle and separating element. The cone extended 50mm from the cable bundle onto the separating element, and 70mm along the cable bundle. |

|                            |                              |
|----------------------------|------------------------------|
| <b>Structural adequacy</b> | <b>Not applicable</b>        |
| <b>Integrity</b>           | <b>No failure at 123 min</b> |
| <b>Insulation</b>          | <b>No failure at 123 min</b> |

## 6. Photos

---

Unexposed faced:



Exposed face:

